

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Application No.: 09/665821

Case No.: 55824US002

Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Please amend claims 2 and 13, and add new claims 30-32, such that the status of the claims is as follows:

1. (Canceled)
2. (Currently amended) An adjustable keyboard tray for use with a center mount bracketing mechanism that is secured to and translates in and out from a horizontal surface, the adjustable keyboard tray comprising:
 - a top plate made of polymeric material;
 - a bottom plate made of polymeric material that is secured to the top plate; and
 - a mounting plate that secures the adjustable keyboard tray to the bracketing mechanism, wherein the mounting plate is secured to a bottom surface of the bottom plate of the adjustable keyboard tray in a recessed mounting area of the bottom plate to maintain a substantially smooth outer surface along the bottom plate.
3. (Previously presented) An adjustable keyboard tray for use with a center mount bracketing mechanism that is secured to and translates in and out from a horizontal surface, the adjustable keyboard tray comprising:
 - a top plate made of polymeric material;
 - a bottom plate made of polymeric material that is secured to the top plate; and
 - a mounting plate that secures the adjustable keyboard tray to the bracketing mechanism, wherein the mounting plate is secured to the adjustable keyboard tray by a retaining bracket, such that the adjustable keyboard tray can slide in a lateral direction substantially perpendicular to the direction of translation by the bracketing mechanism.
4. (Original) The adjustable keyboard tray of claim 3, wherein the retaining bracket is mounted to

Application No.: 09/665821

Case No.: 55824US002

a recessed mounting area formed along a bottom surface of the bottom plate creating a channel therebetween that secures the mounting plate therein and allows the mounting plate to slide thereon, the retaining bracket including a central opening through which the mounting bracket is mounted to the bracketing mechanism and maintaining a substantially smooth outer bottom surface of the adjustable keyboard tray.

5. (Original) The adjustable keyboard tray of claim 4, and further comprising:

a thumb screw aligned to contact and lock the mounting plate in place with respect to the adjustable keyboard tray to prevent lateral movement of the adjustable keyboard tray with respect to the bracketing mechanism.

6. (Previously presented) The adjustable keyboard tray of claim 2 or claim 3, wherein a cavity is formed between the top and the bottom plates.

7. (Original) The adjustable keyboard tray of claim 6, wherein the top and the bottom plates include a series of inner walls along their opposed facing surfaces within the cavity.

8. (Original) The adjustable keyboard tray of claim 7, wherein the top plate and the bottom plate are ultrasonic welded along a set of the inner walls.

9. (Original) The adjustable keyboard tray of claim 7, wherein the series of inner walls within the cavity creates a pocket along a side of the adjustable keyboard tray that is aligned with an opening through the side of the adjustable keyboard tray to receive and secure therein a mouse bracket which supports a mouse platform.

10. (Original) The adjustable keyboard tray of claim 9, wherein the mouse bracket is releasably secured in the pocket by a tab which extends out from one of the inner walls that creates the pocket and is received in a slot on the mouse bracket.

11. (Canceled)

Application No.: 09/665821

Case No.: 55824US002

12. (Previously presented) The adjustable keyboard tray of claim 13 or claim 14, wherein the mouse bracket is releasably secured in the pocket by a tab which extends out from one of the inner walls that creates the pocket and is received in a slot on the mouse bracket.

13. (Currently amended) An adjustable keyboard tray for use with a bracketing mechanism that is secured to and translates in and out from a horizontal surface, the adjustable keyboard tray comprising:

- a top plate made of polymeric material;
- a bottom plate made of polymeric material that is secured to the top plate;
- a cavity between the top plate and the bottom plate;
- a series of inner walls that extend from the top and the bottom plates along their opposed facing surfaces, wherein the inner walls create an inner pocket along a side of the adjustable keyboard tray;
- an opening along the side the adjustable keyboard tray that is aligned with the pocket to provide access therein;
- a mouse bracket that supports a mouse platform, wherein the mouse bracket is inserted into the opening and is received and secured in the pocket; and
- a mounting plate that secures the adjustable keyboard tray to the bracketing mechanism, wherein the mounting plate is secured to a bottom surface of the bottom plate of the adjustable keyboard tray in a recessed mounting area of the bottom plate to maintain a substantially smooth outer surface along the bottom plate.

14. (Previously presented) An adjustable keyboard tray for use with a bracketing mechanism that is secured to and translates in and out from a horizontal surface, the adjustable keyboard tray comprising:

- a top plate made of polymeric material;
- a bottom plate made of polymeric material that is secured to the top plate;
- a cavity between the top plate and the bottom plate;
- a series of inner walls that extend from the top and the bottom plates along their

Application No.: 09/665821

Case No.: 55824US002

opposed facing surfaces, wherein the inner walls create an inner pocket along a side of the adjustable keyboard tray;
an opening along the side the adjustable keyboard tray that is aligned with the pocket to provide access therein;
a mouse bracket that supports a mouse platform, wherein the mouse bracket is inserted into the opening and is received and secured in the pocket; and
a mounting plate that secures the adjustable keyboard tray to the bracketing mechanism, wherein the mounting plate is secured to the adjustable keyboard tray by a retaining bracket, such that the adjustable keyboard tray can slide in a lateral direction substantially perpendicular to the direction of translation by the bracketing mechanism.

15. (Original) The adjustable keyboard tray of claim 14, wherein the retaining bracket is mounted to a recessed mounting area formed along a bottom surface of the bottom plate creating a channel therebetween that secures the mounting plate therein and allows the mounting plate to slide thereon, the retaining bracket including a central opening through which the mounting bracket is mounted to the bracketing mechanism and maintaining a substantially smooth outer bottom surface of the adjustable keyboard tray.

16. (Original) The adjustable keyboard tray of claim 15, and further comprising:
a thumb screw aligned to contact and lock the mounting plate in place with respect to the adjustable keyboard tray to prevent lateral movement of the adjustable keyboard tray with respect to the bracketing mechanism.

17. (Previously presented) The adjustable keyboard tray of claim 14, wherein the top plate is secured to the bottom plate by ultrasonic welding along a set of the inner walls.

18. (Canceled)

19. (Previously presented) The adjustable keyboard tray of claim 20, wherein the top plate is secured to the bottom plate by ultrasonic welding along a set of the inner walls.

Application No.: 09/665821

Case No.: 55824US002

20. (Previously presented) An adjustable keyboard tray for use with a center mount bracketing mechanism that is secured to and translates in and out from a horizontal surface, the adjustable keyboard tray comprising:

- a top plate made of polymeric material;
- a bottom plate made of polymeric material that is secured to the top plate;
- a retaining bracket that is secured to the bottom plate in a manner that creates a channel between the retaining bracket and the bottom plate;
- a central opening in the retaining bracket; and

a mounting plate that is secured in the channel between the retaining bracket and the bottom plate, wherein the mounting plate secures the adjustable keyboard tray to the bracketing mechanism through the central opening in the retaining bracket and slides along the channel such that the adjustable keyboard tray can slide in a lateral direction substantially perpendicular to the direction of translation by the bracketing mechanism, wherein the retaining bracket is mounted to a recessed mounting area formed along a bottom surface of the bottom plate to maintain a substantially smooth outer bottom surface of the adjustable keyboard tray.

21. (Original) The adjustable keyboard tray of claim 20, and further comprising:

- a thumb screw aligned to contact and lock the mounting plate in place with respect to the adjustable keyboard tray to prevent lateral movement of the adjustable keyboard tray with respect to the bracketing mechanism.

22. (Previously presented) The adjustable keyboard tray of claim 20, wherein a cavity is formed between the top and the bottom plates.

23. (Original) The adjustable keyboard tray of claim 22, wherein the top and the bottom plates include a series of inner walls along their opposed facing surfaces within the cavity.

24. (Original) The adjustable keyboard tray of claim 23, wherein the top plate and the bottom plate are ultrasonic welded along a set of the inner walls.

Application No.: 09/665821

Case No.: 55824US002

25. (Original) The adjustable keyboard tray of claim 23, wherein the series of inner walls within the cavity creates a pocket along a side of the adjustable keyboard tray that is aligned with an opening through the side of the adjustable keyboard tray to receive and secure therein a mouse bracket which supports a mouse platform.

26. (Original) The adjustable keyboard tray of claim 25, wherein the mouse bracket is releasably secured in the pocket by a tab which extends out from one of the inner walls that creates the pocket and is received in a slot on the mouse bracket.

27. (Previously presented) A method of repositioning an adjustable keyboard tray in a lateral direction substantially perpendicular to a center mount bracketing mechanism that is secured to a horizontal surface at one end and the adjustable keyboard tray at an opposite end, the method comprising:

pulling the adjustable keyboard out from under the horizontal surface, causing the bracketing mechanism to translate out from under the horizontal surface, wherein the adjustable keyboard tray has a top and a bottom plate that are bonded together;

loosening a screw that passes through a through hole in the top plate and is retained in a threaded bore formed in the bottom plate, so that the screw does not prevent lateral movement of the adjustable keyboard tray ;

repositioning the adjustable keyboard tray in the lateral direction until the adjustable keyboard tray is in a desired position; and

tightening the screw by driving it through the threaded bore until it prevents lateral movement of the adjustable keyboard tray.

28. (Previously presented) The adjustable keyboard tray of claim 2, wherein the top and bottom plates are secured together by ultrasonic welding.

29. (Previously presented) The adjustable keyboard tray of claim 3, wherein the top and

Application No.: 09/665821

Case No.: 55824US002

bottom plates are secured together by ultrasonic welding.

30. (New) An adjustable keyboard tray for use with a center mount bracketing mechanism that is secured to and translates in and out from a horizontal surface, the adjustable keyboard tray comprising:

- a top plate made of polymeric material;
- a bottom plate made of polymeric material that is secured to the top plate such that the top and bottom plates form a cavity therebetween;
- wherein the top and bottom plates include a plurality of inner walls along their opposed facing surfaces that are ultrasonically welded together; and
- a mounting plate that secures the adjustable keyboard tray to the bracketing mechanism.

31. (New) The adjustable keyboard tray of claim 30, wherein the series of inner walls within the cavity creates a pocket along a side of the adjustable keyboard tray that is aligned with an opening through the side of the adjustable keyboard tray to receive and secure therein a mouse bracket which supports a mouse platform.

32. (New) The adjustable keyboard tray of claim 30, wherein the mouse bracket is releasably secured in the pocket by a tab which extends out from one of the inner walls that creates the pocket and is received in a slot on the mouse bracket.